

cpc CHIEFTEK PRECISION Co., LTD.

cpcRobot

6 - axis robot



cpc CHIEFTEK PRECISION Co., LTD.

HEADQUARTERS
CHIEFTEK PRECISION Co., LTD.
No.3, Dali 1st Rd., Xinsi Dist., Southern Taiwan
Science Park, Tainan City, 741-45, Taiwan (R.O.C)
TEL:+886-6-505 5858 Http://www.chieftek.com
E-mail:service@mail.chieftek.com

CHIEFTEK PRECISION USA
2280 E. Locust Court.
Ontario, CA 91761, USA
Tel:+1-909-773-1200
Fax:+1-909-773-1202

cpc Europa GmbH
Industriepark 314,
D 78244 Göttingen, Germany
TEL:+49-7731-59130-38
FAX:+49-7731-59130-28

CHIEFTEK MACHINERY KUNSHAN Co., LTD.
No.1188, Hongqiao Rd, Kunshan,
Jiangsu, P.R. China
TEL:+86-512-5525 2831
FAX:+86-512-5525 2851



2024.01.23 Printed in Taiwan

cpc is the leading foundation provider to achieve your Industry 4.0 vision.

* CPC reserves the right to revise any information(technical details) any time without notice,
for printing mistakes or any other incidental mistakes. We take no responsibility.

The current five significant trends in the robotics industry are

1. Smart learning.
2. Autonomous movement.
3. Implement into new markets.
4. Energy saving.
5. Reduce reliance on labor.

cpc Chieftek Precision Co., Ltd. has always been an essential player in the industrial supply chain. cpc uses self-developed DD motors, mechanical components, drives, and encoders to provide small-sized robotic arms in the market to achieve automation goals in energy saving, mobility, and new market applications.

Tired of the unchangeable production lines?

Rearranging production lines anytime you want to?




Executing multiple different commands at the same time?

**Let cpc's miniature robots help you!
Super small & super light! Your best choice to maximize the flexibility and efficiency of your production lines!**



S0 6 - axis robot

- Small footprint
- Lightweight
- Class-leading repeatability
- Collaborative
- Folding design
- Low noise
- Class-leading torque motor
- High performance servo drive
- High resolution optical absolute encoder
- Brakes in all axes
- Internal cable arrangement
- Tool I/O port
- Side connection / Bottom connection




Specifications



Item	Unit	S0	
Rated payload	kg	0.5	
***Max. payload	kg	1	
Reach	Vertical	mm	446
	Horizontal	mm	370
*Repeatability	µm	+/- 10	
Weight	kg	4	
Power supply	V,A	48 Vdc, 5A	
Brakes	Axis	1,2,3,4,5,6	
Communication		TCP/IP, Modbus TCP to controller/ EtherCAT to robot	
Max. motion range	J1 (Base)	+/- 360°	
	J2 (Shoulder)	+/- 360°	
	J3 (Elbow)	+/- 360°	
	J4 (Wrist)	+/- 360°	
	J5 (Wrist)	+/- 360°	
	J6 (Wrist)	Infinite	
**Max. speed	J1 (Base)	180°/sec	
	J2 (Shoulder)	154°/sec	
	J3 (Elbow)	180°/sec	
	J4 (Wrist)	288°/sec	
	J5 (Wrist)	324°/sec	
	J6 (Wrist)	324°/sec	
*Max. TCP speed	mm/s	600	
IP protection rating		IP54	
Product Safety Certification		EN ISO 12100 EN ISO 10218-1 EN 60204-1 EN ISO 13849-1 ISO/TS 15066 ISO/DIS 10218-1.2	

* When the temperature of the robot is constant.
 ** The maximum speed depends on the center of mass offset.
 *** Available to 80% motion area.

■ Motion area





Dimensions





The S0 is the smallest collaborative robotic arm on the market today, with an arm weight of just 4kg and a maximum payload of 1 kg. The small size and light weight allow S0 to move flexibly even in the narrow space and can change the best mode and position at any time to meet the needs of the production line. The unique folding design creates multiple path planning opportunities for greater movement efficiency.

S0 power/signal input and MCS Coordinate System

Side connection




Bottom connection



MCS Coordinate System


S0 end connection dimensions and TCS coordinate System

Unit : mm



TCS Coordinate System

Tool I/O port



Pin definition

Number	Definition	Description
1	Grounding	Grounding
2	AI-0	analog input (0~10V)
3	DI-0	digital input
4*	DO-0 or power or ground	Digital output or 0/12/24 V or ground
5	Power	0/12/24 V
6	AI-1	analog input (0~10V)
7	DI-1	digital input
8*	DO-1 or power or ground	Digital output or 0/12/24 V or ground

* The user can set the output signal as PNP, NPN, or pull/push via the interface.




DBO 6 - axis robot

- Small footprint
- Lightweight
- Class-leading repeatability
- Industrial
- Folding design
- Low noise
- Class-leading torque motor
- High performance servo drive
- High resolution optical absolute encoder
- Brakes in J1, J2, J3 and J4 axes
- Internal cable arrangement
- High rigidity
- Tool I/O port
- Side connection / Bottom connection



Teach-in panel



DBO is a compact, 4.7 kg weight 6-axis robot arm with high rigidity. These features create high precise motion and operate in limited space with optimal usage. 5 μ m repeatability makes higher precision mission to be done. DBO also provides a guided panel to complete the path planning easily.

Specifications

Item	Unit	DBO	
Payload	kg	0.5	
Reach	Vertical	mm	465
	Horizontal	mm	327
*Repeatability	μ m	+/- 5	
Weight	kg	4.7	
Power supply	V,A	48 Vdc, 5A	
Brakes	Axis	1,2,3,4	
Communication		TCP/IP, Modbus TCP to controller/ EtherCAT to robot	
IP protection rating		IP40	
Product Safety Certification		EN ISO 12100 EN ISO 10218-1 EN 60204-1 EN ISO 13849-1 ISO/DIS 10218-1.2	




Item	Unit	DBO
Max. motion range	J1 (Base)	+ 175° / - 175°
	J2 (Shoulder)	+ 160° / - 15°
	J3 (Elbow)	+ 145° / - 80°
	J4 (Wrist)	+ 175° / - 175°
	J5 (Wrist)	+ 90° / - 90°
	J6 (Wrist)	Infinite
**Max. speed	J1 (Base)	180°/sec
	J2 (Shoulder)	180°/sec
	J3 (Elbow)	180°/sec
	J4 (Wrist)	360°/sec
	J5 (Wrist)	360°/sec
	J6 (Wrist)	360°/sec
*Max. TCP speed	mm/s	1000

* When the temperature of the robot is constant.
** The maximum speed depends on the center of mass offset.

Dimensions


■ Motion area

Unit: mm




DB0 power/signal input and MCS Coordinate System


Side connection




Bottom connection



DB0 end connection dimensions and TCS coordinate System



Tool I/O port



Pin definition

Number	Definition	Description
1	Grounding	Grounding
2	AI-0	analog input (0~10V)
3	DI-0	digital input
4*	DO-0 or power or ground	Digital output or 0/12/24 V or ground
5	Power	0/12/24 V
6	AI-1	analog input (0~10V)
7	DI-1	digital input
8*	DO-1 or power or ground	Digital output or 0/12/24 V or ground

* The user can set the output signal as PNP, NPN, or pull/push via the interface.

Robot Ordering information

S	0	N	03	S	G	J	Customization
							Tool I/O Signal: G: Typical I/O EC : EtherCAT
							The rotation angle of the final axis: M: unlimited S: ±360°
							Cable length: 03:3 m 12:12 m
							Connection direction: N- side direction B- bottom direction
							Size : 0
							Product type : DB : Industrial S : Collaborative

Accessories



IPC Controller
(Lex SKY2 2I640DW)



Power Supplier: 10A@48VDC




E-stop

cpcRobot Features


Interpreter

The robotic arm interpreter is a specialized editor for crafting motion programs. Developers can expedite programming and streamline motion verification by simply clicking instructions, configuring settings, and inserting code.




Collision Detection

The cpc robotic arm collision detection system employs mathematical models to sense collision during execution of tasks, eliminating the need for external sensors. It covers both the arm and the tool, with sensitivity adjustments available on a dedicated interface for ease of use and configuration.



Dimensional Dragging Constraints

In zero-gravity mode, dimensions for free dragging can be specified, including lines and planes.




Hand-Guided Teaching

Hand-guided teaching is an intuitive method for editing robotic arm paths, bypassing the need for complex programming languages. By manually moving the robotic arm, required actions are recorded in real-time, empowering non-technical personnel to effectively employ robotic arms for diverse tasks.



Simulator

The simulator faithfully reproduces robotic arm motion, enabling users to test, verify, and optimize tasks without impacting the physical arm. It offers single-joint operation and Speed Override features, serving as a safe and efficient simulation tool for developing and testing robotic arm applications.



cpcRobot Features

Automated Tool Dimension Calculation




The automated tool dimension calculation feature automatically calculates end-of-arm tool dimensions, reducing manual input, minimizing errors, and enhancing user experience in robotic arm applications.



API and SDK Support



The robotic arm system supports API (Application Programming Interface) and SDK (Software Development Kit), enabling developers to write functions using C, C++, and custom languages. By offering APIs and SDKs, it becomes an open and flexible platform, simplifying robotic arm integration into developers' applications.



Automatic PCS Coordinate System Configuration



The automatic PCS Coordinate System Configuration feature automatically calculates and sets the robotic arm's coordinate system, including reference points, directions, and related parameters. This simplifies adaptation to various work scenarios and tasks while reducing operator configuration workload.



EtherCAT Automatic Configuration



EtherCAT automatic configuration automatically recognizes and configures specified devices on EtherCAT, saving time, simplifying the process, and ensuring configuration accuracy.


Tablet App





cpcRobot offers an Android app for remote operation, functioning as a teaching tool for users to perform tasks including program editing, numerical monitoring, manual operations, and teaching.



Collaborate with a third-party PLC



Using cpcStudio



Package selection SO/DBO

controller	Interpreter	c#/c++ API	Android APP	IEC 61131-3 PLC Language	EtherCAT	OPC UA	Motion Library
Controller *1 Power cable 3m *1 EtherCAT cable 3m *1 Power supplier *1	Robot Motion Control EtherCAT SDO Command Modbus Command User Defined Command Math Library Bitwise Operation Flow Control	Support to c#/C++ programming	Wifi APP	Follow IEC 61131-3	Free configuration EtherCAT slave	Support to OPC-UA	One/Multiple Axes.

A PACKAGE



B PACKAGE



C PACKAGE



D PACKAGE



Package selection SO / DBO

E PACKAGE



F PACKAGE



G PACKAGE



H PACKAGE



I PACKAGE



ATC Automatic Tool Changer System

ATC Automatic tool change system

In the process of automation, robot arms are increasingly required to perform multitasking to optimize the use of simple design and space efficiency. Therefore, automatic tool change can greatly reduce downtime and tool change time in the robot system. It is seen as an essential requirement to increase production capacity. Direct Technology has launched an automatic tool change system for micro-robots, including the holder, tool/robot joint, and various connectors.

Its unique patented design is purely mechanically combined, so it brings the following main feature:

1. Quick and easy

No external air pressure and power are needed, and the tool exchange can be completed during the movement of the robot arm, which simplifies the entire tool change system and saves the time for tool exchange.

2. High reliability

Because it does not rely on extra power sources, there is no need to worry about the instability of the source and can keep the reliability and integration accuracy of the entire tool changer.

3. Lightweight


Compare to the same class, because of no extra adapters; it will not increase the excessive load consumption of the robot arm.

4. Magnet support guiding : all directions mechanical fixing

Using the permanent magnet to fix the connecting plate and the tool holder greatly reduces the risk of mechanical wear.

5. Provide electrical connector interface / Customization

Provide customized air pressure and electrical connectors to suit the various tools of the different applications.



Tool changing system specifications


Specification	unit	ACT-45
Max. payload	kg	> 2*
Bending force	N	> 200*
XY axis maximum Static moment	Nm	> 30*
Z axis maximum Static moment	Nm	> 30*
Weight	kg	0.068
Repeatability	mm	+/- 0.01
Electrical I/O	-	8x1A@24 Vdc

* For the maximum value that can be tolerated, please get in touch with **cpc** team.

Tool changing mechanism - tool / fixture connecting plate


Robot side :

Robot plate dimensions




Robot plate connecting plate

Robot plate input interface



Pogo pin




The relationship between the pins and the wiring


input interface	output interface
Pogo pin / No.	Flying wire / Color
1	brown
2	gray
3	blue
4	yellow
5	red
6	pink
7	green
8	white

tool side :


Tool plate dimensions





Tool plate output interface



Tool holder



Tool changer installation and setting



VA Vacuum gripper

Tool changer ordering information

ATC	45	M	P	F	N	01	J	
								Customization
								Cable length: 01 : 0.1 m N : none
								Air pressure connector: N: none
								Output electrical interface: F: Flying wire C: M8 connector
								Input electrical interface: P : Pogo pin F : Flying wire C : M8 connector
								Part: M: Robot plate T: Tool plate H: Tool holder K: Kit
								Size : 45
								Product type : ATC Automatic tool change system

VA Vacuum gripper

VA is a compact integrated vacuum gripper that includes a vacuum pump, pressure detector, and solenoid valve to form a complete vacuum cycle system. Users don't need to prepare a vacuum source. Since there is no tracheal distribution, using the gripper with the arm will avoid the problem of entanglement in the past.


In addition, the vacuum pump, air pressure detector, and solenoid valve can be controlled independently. The user can determine the optimal process for operating the gripper. The VA vacuum gripper can be installed directly on the cpcRobot and ATC automatic tool changing system to achieve plug-and-play function.

Features

- Plug and play function
- Built-in vacuum ejector, all-electric supply, no need for external pipes.
- Built-in air pressure sensor.
- The pump operation can be controlled freely; therefore, the pump duty cycle can be used efficiently, and the service life can be increased.
- The M5 air pad can be replaced based on application needs. The unused 5xM5 threaded holes must be sealed with set screws. (Customization)

VA Vacuum gripper	
Model	VA-45
Actuation energy	DC power
Weight (kg)	0.23
Maximum suction load (kg)*	0.9
Maximum vacuum pressure (mbar)**	-500
Maximum flow (l/min)**	0.55
Operating temperature (°C)	5-50
Pressure sensor	
Rated pressure range (mbar)	0-1010
Output voltage (V)	1-5

* The suction direction of the standard product is vertical, and the actual use must take into account the diameter of the sucker, the installation direction, and the position of the center of gravity.
 ** This ideal value will depend on atmospheric pressure conditions.




Pin table

Number	Function	Wire diameter	color
1	24V	28 AWG	white
2	DI-1 (Pump switch)	28 AWG	blue
3	DI-0 Vacuum no/off	28 AWG	pink
4	DO-1	28 AWG	gray
5	DO-0	28 AWG	yellow
6	AO-1	28 AWG	green
7	AO-0 (Pressure sensing)	28 AWG	brown
8	GND	28 AWG	red

VA Vacuum gripper ordering information

VA	45	S	15	03	-J	Customization*
Cable length : 03 : 3m						
Air pad diameter : Ø8x5 Max. Ø10x4 Max. Ø15x4 Max.						
Number of Air pad: S: Standard O: None						
size : 45						
Production type: VA Vacuum gripper						

*Note: The user can design the customized mounting hole of the pad and positioning hole on VA gripper.



Not only for users, but also for designers
cpc's products inspire you!
 Together with cpc to achieve new levels of innovation!